



### SMALL STRUCTURE SIGN

Scale: None

#### Placement Notes:

1. The small structure sign shall be placed behind traffic barriers where applicable, (delineator post to be driven within traffic barrier w-beam post). The sign shall be placed at the approach ends of the structure on the right side of the road, at roadway level.
2. Divided highways shall have only one sign placed at each approach end.
3. If traffic barriers are not present, place small structure sign as close to end of structure as possible but sign must be visible from the approach roadway.
4. For noise walls and retaining walls place one small structure sign at each end.
5. For retaining walls that are not visible from the approach roadway, place small structure sign as close to end of structure as possible but sign must be visible from approach roadway. For retaining walls that are visible from the approach roadway, refer to M(0.06)-99-333.
6. Always locate small structure sign so that it will be in the safest position possible relative to highway and pedestrian traffic.

APPROVAL	
<i>L. S. Friedman</i> DIRECTOR OFFICE OF BRIDGE DEVELOPMENT	
DATE: 7/18/00	
REVISIONS	
SHA	FHWA
3-20-01	-
9-20-05	-
FHWA APPROVAL	-
DATE:	-

STATE OF MARYLAND  
DEPARTMENT OF TRANSPORTATION  
STATE HIGHWAY ADMINISTRATION  
OFFICE OF BRIDGE DEVELOPMENT

### SMALL STRUCTURE SIGN AND PLACEMENT DETAILS

STANDARD NO. BR-MAINT(0.02)-00-339

SHEET 1 OF 1